

Primary Specifications

BTUs	34000
Refrigerant	410A
Hertz	60
Phase	1
Voltage	208/230
Oil	POE
Application	AIR CONDITIONING

Performance

Discharge/Suction Temp	50/115	50/100
RG./Liq (Fahrenheit)	70/100	70/85
BTUs per hour	42400	46500
Watts	2640	2160
Current/Amps	11.45	9.7

Additional Information

Oil Charge	42
Oil Recharge	36
Discharge (in)	1/2 STUB
Suction (in)	7/8 STUB

Electrical Information

LRA (Locked Rotor Amps)	109
MCC (Amps)	26
Max Operating Current	18.2
Run Load Amps Contactor	13
Run Load Amps Breaker & Wire	11.7
Run Capacitor (MFD)	45
Run Capacitor Voltage	45
Start Capacitor (MFD)	88
Start Capacitor Voltage	330

Dimensions

Mounting Length/Width (in)	7.5
Mounting Height (in)	17.17
Overall Length/Width (in)	9.56
Overall Height (in)	16.94
Net Weight (Lbs)	71.7



ARRCO Model Number Nomenclature Guide

Example Model # AR34KCM-BMV

A	ARRCO, LLC.					
R	Refrigerant R = R22,R407C A = 410A					
34	Nominal Capacity (BTU/h) @ 60 Hz 34 = 34,000 BTU/h 150 = 150,000 BTU/h					
KC	Model Variation					
M	Oil Type M = Mineral oil P = POE oil					
B	Phase B = Single phase, capacitor required permanent split capacitor H = Three phase, 3 lead single voltage/6 lead part winding					
M	Protection F = Internal motor protection, use with contactor W = External electronic protection					
V	Voltage	60 Hz.	50 Hz.	Voltage	60 Hz.	50 Hz.
C		208/230-3	200-3	V	208/230-1	
D		460-3	380/420-3	X		
E		575-3		5	200/230-3	200/220-3
J		265-1	220/240-1	7	380-3	
M			380/420-3	Z		220/240-1
R			220/240-3			

Disclaimer: All data shown above is subject to change and may be incorrect. To get accurate official data of compressor characteristics please contact us directly.