

Primary Specifications

BTUs	16000
Refrigerant	R407C
Hertz	60
Phase	1
Voltage	208/230
Oil	MINERAL
Application	AIR CONDITIONING

Performance

Discharge/Suction Temp	50/100	45/130
RG./Liq (Fahrenheit)	70/85	65/115
BTUs per hour	20300	15500
Watts	995	1485
Current/Amps	4.25	6.3

Additional Information

Oil Charge	25
Oil Recharge	19
Discharge (in)	1/2 STUB
Suction (in)	3/4 STUB

Electrical Information

LRA (Locked Rotor Amps)	40.3
MCC (Amps)	13
Max Operating Current	9
Run Load Amps Contactor	
Run Load Amps Breaker & Wire	
Run Capacitor (MFD)	30
Run Capacitor Voltage	30
Start Capacitor (MFD)	88
Start Capacitor Voltage	330

Dimensions

Mounting Length/Width (in)	7.5
Mounting Height (in)	7.5
Overall Length/Width (in)	9.5
Overall Height (in)	9.5
Net Weight (Lbs)	47.7



ARRCO Model Number Nomenclature Guide

Example Model # AR34KCM-BMV

A	ARRCO, LLC.					
R	Refrigerant R = R22,R407C A = 410A					
34	Nominal Capacity (BTU/h) @ 60 Hz 34 = 34,000 BTU/h 150 = 150,000 BTU/h					
KC	Model Variation					
M	Oil Type M = Mineral oil P = POE oil					
B	Phase B = Single phase, capacitor required permanent split capacitor H = Three phase, 3 lead single voltage/6 lead part winding					
M	Protection F = Internal motor protection, use with contactor W = External electronic protection					
V	Voltage	60 Hz.	50 Hz.	Voltage	60 Hz.	50 Hz.
	C	208/230-3	200-3	V	208/230-1	
	D	460-3	380/420-3	X		
	E	575-3		5	200/230-3	200/220-3
	J	265-1	220/240-1	7	380-3	
	M		380/420-3	Z		220/240-1
	R		220/240-3			

Disclaimer: All data shown above is subject to change and may be incorrect. To get accurate official data of compressor characteristics please contact us directly.