

Primary Specifications

BTUs	22000
Refrigerant	R407C
Hertz	50
Phase	3
Voltage	380/420
Oil	MINERAL
Application	AIR CONDITIONING

Performance

Discharge/Suction Temp	45/100	45/130
RG./Liq (Fahrenheit)	65/85	65/115
BTUs per hour	21500	18200
Watts	1170	1760
Current/Amps	2.5	3.2

Additional Information

Oil Charge	38
Oil Recharge	34
Discharge (in)	1/2 STUB
Suction (in)	3/4 STUB

Electrical Information

LRA (Locked Rotor Amps)	24
MCC (Amps)	5.5
Max Operating Current	4.2
Run Load Amps Contactor	
Run Load Amps Breaker & Wire	
Run Capacitor (MFD)	0
Run Capacitor Voltage	0
Start Capacitor (MFD)	0
Start Capacitor Voltage	0

Dimensions

Mounting Length/Width (in)	7.5
Mounting Height (in)	15.07
Overall Length/Width (in)	9.69
Overall Height (in)	14.84
Net Weight (Lbs)	54.1



ARRCO Model Number Nomenclature Guide

Example Model # AR34KCM-BMV

A	ARRCO, LLC.																																										
R	Refrigerant R = R22,R407C A = 410A																																										
34	Nominal Capacity (BTU/h) @ 60 Hz 34 = 34,000 BTU/h 150 = 150,000 BTU/h																																										
KC	Model Variation																																										
M	Oil Type M = Mineral oil P = POE oil																																										
B	Phase B = Single phase, capacitor required permanent split capacitor H = Three phase, 3 lead single voltage/6 lead part winding																																										
M	Protection F = Internal motor protection, use with contactor W = External electronic protection																																										
V	<table border="1"> <thead> <tr><th>Voltage</th><th>60 Hz.</th><th>50 Hz.</th><th>Voltage</th><th>60 Hz.</th><th>50 Hz.</th></tr> </thead> <tbody> <tr><td>C</td><td>208/230-3</td><td>200-3</td><td>V</td><td>208/230-1</td><td></td></tr> <tr><td>D</td><td>460-3</td><td>380/420-3</td><td>X</td><td></td><td></td></tr> <tr><td>E</td><td>575-3</td><td></td><td>5</td><td>200/230-3</td><td>200/220-3</td></tr> <tr><td>J</td><td>265-1</td><td>220/240-1</td><td>7</td><td>380-3</td><td></td></tr> <tr><td>M</td><td></td><td>380/420-3</td><td>Z</td><td></td><td>220/240-1</td></tr> <tr><td>R</td><td></td><td>220/240-3</td><td></td><td></td><td></td></tr> </tbody> </table>	Voltage	60 Hz.	50 Hz.	Voltage	60 Hz.	50 Hz.	C	208/230-3	200-3	V	208/230-1		D	460-3	380/420-3	X			E	575-3		5	200/230-3	200/220-3	J	265-1	220/240-1	7	380-3		M		380/420-3	Z		220/240-1	R		220/240-3			
Voltage	60 Hz.	50 Hz.	Voltage	60 Hz.	50 Hz.																																						
C	208/230-3	200-3	V	208/230-1																																							
D	460-3	380/420-3	X																																								
E	575-3		5	200/230-3	200/220-3																																						
J	265-1	220/240-1	7	380-3																																							
M		380/420-3	Z		220/240-1																																						
R		220/240-3																																									

Disclaimer: All data shown above is subject to change and may be incorrect. To get accurate official data of compressor characteristics please contact us directly.