

Primary Specifications

BTUs	48000
Refrigerant	R407C
Hertz	60
Phase	3
Voltage	575
Oil	MINERAL
Application	AIR CONDITIONING

Performance

Discharge/Suction Temp	45/100	45/130
RG./Liq (Fahrenheit)	65/85	65/115
BTUs per hour	58000	49100
Watts	3080	4270
Current/Amps	3.8	5

Additional Information

Oil Charge	46
Oil Recharge	42
Discharge (in)	1/2 STUB
Suction (in)	7/8 STUB

Electrical Information

LRA (Locked Rotor Amps)	37
MCC (Amps)	9
Max Operating Current	8.5
Run Load Amps Contactor	
Run Load Amps Breaker & Wire	
Run Capacitor (MFD)	0
Run Capacitor Voltage	0
Start Capacitor (MFD)	0
Start Capacitor Voltage	0

Dimensions

Mounting Length/Width (in)	7.5
Mounting Height (in)	17.18
Overall Length/Width (in)	9.69
Overall Height (in)	16.94
Net Weight (Lbs)	76



ARRCO Model Number Nomenclature Guide

Example Model # AR34KCM-BMV

A	ARRCO, LLC.					
R	Refrigerant R = R22,R407C A = 410A					
34	Nominal Capacity (BTU/h) @ 60 Hz 34 = 34,000 BTU/h 150 = 150,000 BTU/h					
KC	Model Variation					
M	Oil Type M = Mineral oil P = POE oil					
B	Phase B = Single phase, capacitor required permanent split capacitor H = Three phase, 3 lead single voltage/6 lead part winding					
M	Protection F = Internal motor protection, use with contactor W = External electronic protection					
V	Voltage	60 Hz.	50 Hz.	Voltage	60 Hz.	50 Hz.
C		208/230-3	200-3	V	208/230-1	
D		460-3	380/420-3	X		
E		575-3		5	200/230-3	200/220-3
J		265-1	220/240-1	7	380-3	
M			380/420-3	Z		220/240-1
R			220/240-3			

Disclaimer: All data shown above is subject to change and may be incorrect. To get accurate official data of compressor characteristics please contact us directly.